

TRANSFO-02

600 V → 480 V / 120-208 V – 45 kVA + 30 kVA

POWER SOLUTIONS

TECHNICAL SPECIFICATIONS	
RATED POWER	75 kVA total (45 kVA + 30 kVA)
INPUT VOLTAGE	600 V AC – 3 PHASE – 60 A (SHARED PRIMARY DISCONNECT)
OUTPUT VOLTAGE	480 V AC – 3 PHASE – 30 A / 50 A • 120/208 V AC – 1 PHASE – 20 A / 30 A
PRIMARY DISCONNECT	60 A (FUSED, SHARED BETWEEN BOTH TRANSFORMERS)
SECONDARY DISCONNECT / MAIN BREAKER	30 A / 50 A (480 V) • 1P 20 A / 2P 30 A (120/208 V)
FREQUENCY	60 Hz



VERSATILE DUAL-OUTPUT TRANSFORMER FOR DEMANDING JOB SITES

DUAL-VOLTAGE POWER SOURCE

- 600V → 480V (45 kVA) for grinders, vacuums, and heavy-duty equipment.
1 × 480V 50A
and 1 × 480V 30A.
- 600V → 120/208V (30 kVA) for auxiliary tools and devices.
4 × 120V 20A GFI
1 × 208V 30A single-phase
and 1 × 208V 30A three-phase.

INTEGRATED AND SAFE PROTECTION

A single shared primary disconnect powers both modules, with dedicated secondary breakers for each output.

ALL-IN-ONE INSTALLATION

Delivers complete job-site power from a single compact unit, reducing the need for multiple connections and power sources.

